

APPENDIX G4: FUGITIVE DUST EMISSION ESTIMATES

This appendix provides a summary of fugitive dust emissions that would be generated by military vehicle travel on unpaved roads or on unpaved vehicle maneuver areas under all project alternatives. Emission estimates are presented for travel on gravel roads, dirt roads, and off-road maneuver areas at each installation under each alternative. The summarized emission estimates are based on current AP-42 procedures (EPA 1998). Vehicle use assumptions (consistent with those used for Appendix G3) also are presented.

The detailed spreadsheets documenting the emission calculations generally do not lend themselves to hard copy printing. Electronic versions of the spreadsheets can be made available on request.

SUMMARY OF ESTIMATED PM10 EMISSIONS FROM MILITARY VEHICLE TRAVEL ON UNPAVED AREAS

			NO ACTION		PROPOSED ACTION			REDUCED LAND ACQUISITION		
		ESTIMATED	ANNUAL PM10,	ESTIMATED	ANNUAL PM10,	NET CHANGE,	ESTIMATED	ANNUAL PM10,	NET CHANGE,	
LOCATION	TRAFFIC AREA	ANNUAL VMT	TONS/YEAR	ANNUAL VMT	TONS/YEAR	PM10 TONS/YEAR	ANNUAL VMT	TONS/YEAR	PM10 TONS/YEAR	
Schofield Barracks Main Post	Gravel Roads	165,436	170.74	240,351	295.28	124.54	240,351	295.28	124.54	
Scholicia Bartacks Wall 1 ost	Dirt Roads	56,399	162.19	81,938	280.49	118.30	81,938	280.49	118.30	
	Off-Road Areas	41,279	52.26	67,497	103.34	51.08	67,497	148.71	96.45	
	TOTAL	263,114	385.18	389,786	679.11	293.92	389,786	724.48	339.29	
Schofield Barracks East Range	Gravel Roads	110,291	172.13	160,234	297.68	125.55	160,234	297.68	125.55	
	Dirt Roads	37,599	163.50	54,625	282.77	119.26	54,625	282.77	119.26	
	Off-Road Areas TOTAL	96,319 244,208	139.17 474.80	157,494 372,353	380.81 961.25	241.63 486.45	157,494 372,353	380.81 961.25	241.63 486.45	
	IOIAL	244,208	474.80	372,333	901.23	400.43	372,333	701.23	400.43	
SCHOFIELD SUBTOTAL	Gravel Roads	275,727	342.86	400,585	592.96	250.09	400,585	592.96	250.09	
SCHOFIELD SUBTOTAL	Dirt Roads	93,998	325.69	136,563	563.25	237.56	136,563	563.25	237.56	
	Off-Road Areas	137,598	191.43	224,991	484.15	292.72	224,991	529.52	338.09	
	TOTAL	507,323	859.99	762,139	1,640.36	780.37	762,139	1,685.73	825.74	
	TOTAL	307,020	637.57	702,107	1,040.20	700.57	702,109	1,005.70	023.74	
Dillingham Military Reservation	Gravel Roads	53,876	62.72	62,702	86.89	24.17	62,702	86.89	24.17	
Diffinguali Williary Reservation	Dirt Roads	18,367	59.58	21,376	82.54	22.96	21,376	82.54	22.96	
	Off-Road Areas	181,340	204.03	223,069	367.50	163.48	223,069	367.50	163.48	
	TOTAL	253,582	326.33	307,146	536.94	210.61	307,146	536.94	210.61	
		,		ŕ			, ,			
Kahuku Training Area	Gravel Roads	36,733	42.77	54,302	75.25	32.49	54,302	75.25	32.49	
	Dirt Roads	12,523	40.62	18,512	71.48	30.86	18,512	71.48	30.86	
	Off-Road Areas	123,641	77.31	233,838	329.18	251.87	233,838	329.18	251.87	
	TOTAL	172,897	160.70	306,651	475.91	315.22	306,651	475.91	315.22	
OLI WIL GUIDEOU I	G ID I	266.226	440.25	517 500	755.11	207.75	517.500	755.11	206.75	
O'AHU SUBTOTAL	Gravel Roads	366,336	448.35	517,588	755.11	306.75	517,588	755.11	306.75	
	Dirt Roads Off-Road Areas	124,887 442,579	425.89 472.77	176,451 681,898	717.28 1,180.83	291.39 708.06	176,451 681,898	717.28 1,226.20	291.39 753.43	
	TOTAL	933.802	1,347.01	1,375,936	2,653.21	1,306.20	1,375,936	2,698.58	1,351.57	
	IOIAL	933,802	1,547.01	1,373,930	2,033.21	1,300.20	1,373,930	2,098.38	1,331.57	
Pahukaloa Training Area	Gravel Roads	169,621	344.78	250,049	605.02	260.24	250,049	605.02	260.24	
randkaloa rranning Area	Dirt Roads	57,825	153.84	85,244	269.97	116.12	85,244	269.97	116.12	
	Off-Road Areas	349,727	299.63	661,427	352.71	53.07	661,427	352.71	53.07	
	TOTAL	577,173	798.25	996,720	1,227.69	429.44	996,720	1,227.69	429.44	
	1011112	377,170	170120	220,120	1,227.07	122,111	2203120	1,227.07	322,33	
GRAND TOTAL	Gravel Roads	535,957	793.13	767,637	1,360.13	567.00	767,637	1,360.13	567.00	
0	Dirt Roads	182,713	579.74	261,694	987.25	407.51	261,694	987.25	407.51	
	Off-Road Areas	792,306	772.40	1,343,324	1,533.54	761.13	1,343,324	1,578.90	806.50	
	TOTAL	1,510,976	2,145.27	2,372,656	3,880.91	1,735.64	2,372,656	3,926.28	1,781.01	
	101111	1,010,770	2,170.27	2,0 / 2,000	5,000.71	1,700.01	2,0 / 2,000	5,720.20	1,701.01	

Notes:

Fugitive dust calculations are based on the current EPA AP-42 Section 13.2.2 (1998 equation version), including the low speed adjustment factor. Vegetation cover is used as a linear correction factor for vehicle activity in off-road areas.

Source:

U.S. Environmental Protection Agency. 1998. Compilation of Air Pollutant Emission Factors (AP-42) 5th Edition, Volume I, Supplement E, Section 13.2.2 (Unpaved Roads).

EPA FUGITIVE DUST EQUATIONS FOR UNPAVED ROADS

gallons/liter = 0.264172052 grams/pound = 453.5923745 mile/kilometer = 0.621371192

FUGITIVE DUST FROM UNPAVED AREAS:

Five alternative equations are available for estimating fugitive PM10 from vehicle use on unpaved areas (unpaved roads, tank trails, or off-road areas):

Emission rate equation in AP-42 Fifth Edition, Volume I, Section 13.2.2 (EPA 1995):

 $PM10 \ tons/day = 0.36*5.9*[(\%silt+clay)/12]*(mph/30)*[(tons \ GVW/3)^(0.7)]*[(\#wheels/4)^(0.5)]*[(365-precip \ days)/365]*(VMT/day)/(2000 \ lbs/ton))*[(1000 \ lbs/ton)]*[(1000 \ lbs$

Emission rate equation in AP-42 Fifth Edition, Volume I, Supplement E, Section 13.2.2 (EPA 1998):

PM10 tons/day = $2.6*[((\%silt+clay)/12)^{(0.8)}]*[(mean vehicle weight in tons/3)^{(0.4)}]*[(365-precip days)/365]*(VMT/day)/([(surface moisture %/0.2)^{(0.3)}]*(2000 lbs/ton))$ where "mean vehicle weight in tons" is a weighted average of all vehicle traffic an a particular road segment or off-road area.

Note: this equation overpredicts emissions at speeds below 15 mph. An optional multiplier of (mean vehicle speed)/15 can be used as a correction factor.

Emission rate equation A in proposed revision to AP-42 Fifth Edition, Volume I, Section 13.2.2 (EPA 2001):

PM10 tons/day = $1.5*[((%silt+clay)/12)^{(0.9)}]*[(mean vehicle weight in tons/3)^{(0.45)}]*[(365-precip days)/365]*(VMT/day)/(2000 lbs/ton) where "mean vehicle weight in tons" is a weighted average of all vehicle traffic an a particular road segment or off-road area.$

Emission rate equation B Option 1 in proposed revision to AP-42 Fifth Edition, Volume I, Section 13.2.2 (EPA 2001):

PM10 tons/day = $1.8*[(\%silt+clay)/12]*[(mean vehicle speed in mph/30)^(0.5)]*[(365-precip days)/365]*(VMT/day)/([(surface moisture \%/0.5)^(0.2)]*(2000 lbs/ton)) where "mean vehicle speed in mph" is a weighted average of all vehicle traffic an a particular road segment or off-road area.$

Emission rate equation B Option 2 in proposed revision to AP-42 Fifth Edition, Volume I, Section 13.2.2 (EPA 2001):

PM10 tons/day = $1.7*[((\%silt+clay)/12)^{(0.8)}]*[(mean vehicle speed in mph/30)]*[(365-precip days)/365]*(VMT/day)/([(surface moisture %/0.5)^{(0.2)}]*(2000 lbs/ton))$ where "mean vehicle speed in mph" is a weighted average of all vehicle traffic an a particular road segment or off-road area.

NOTE:

When any of the above equations are applied to off-road vehicle activity that is not on established trails, the percent vegetation cover can be used as an additional linear control factor. The multiplier factor would be (1-vegetation cover fraction).

SUMMARY OF MILITARY VEHICLE DRIVING ESTIMATES PAVED ROADS, UNPAVED ROADS, AND OFF-ROAD AREAS

PAVED ROAD TRAVEL ANALYSIS

NOMINAL		CUMULATIVE	PERCENT
ALTERNATIVE	LOCATION	VEH-HOURS	OF TOTAL
PROPOSED ACTION	SCHOFIELD	8,292	60.00%
	DMR	2,030	14.69%
	KTA	1,225	8.86%
	SUBTOTAL	11,546	83.55%
	PTA	2,274	16.45%
	TOTAL	13,820	100.00%
REDUCED LAND	SCHOFIELD	8,292	60.00%
ACQUISITION	DMR	2,030	14.69%
·	KTA	1,225	8.86%
	SUBTOTAL	11,546	83.55%
	PTA	2,274	16.45%
	TOTAL	13,820	100.00%
NO ACTION	SCHOFIELD	5,863	59.13%
No herion	DMR	1,642	16.56%
	KTA	704	7.10%
	SUBTOTAL	8,208	82.78%
	PTA	1,707	17.22%
	TOTAL	9,916	100.00%
	TOTAL	<i>)</i> ,,/10	100.00 /0

Notes:

Vehicle idling time for paved road travel set at 5% of the cumulative driving time.

Vehicle load conditions for Strykers and HMMWVs set at 75% intermediate and 25% maximum.

Vehicle load conditions for trucks set at 50% empty, 40% loaded, 10% max load.

UNPAVED ROAD TRAVEL ANALYSIS

	NOMINAL	CUMULATIVE	PERCENT
ALTERNATIVE	LOCATION	VEH-HOURS	OF TOTAL
PROPOSED ACTION	SCHOFIELD	27,313	52.18%
	DMR	4,275	8.17%
	KTA	3,702	7.07%
	SUBTOTAL	35,290	67.43%
	PTA	17,049	32.57%
	TOTAL	52,339	100.00%
REDUCED LAND	SCHOFIELD	27,313	52.18%
ACQUISITION	DMR	4,275	8.17%
	KTA	3,702	7.07%
	SUBTOTAL	35,290	67.43%
	PTA	17,049	32.57%
	TOTAL	52,339	100.00%
NO ACTION	SCHOFIELD	18,800	51.45%
	DMR	3,673	10.05%
	KTA	2,505	6.85%
	SUBTOTAL	24,977	68.35%
	PTA	11,565	31.65%
	TOTAL	36,543	100.00%

Notes:

Vehicle idling time for unpaved road travel set at 15% of the cumulative driving time.

Vehicle load conditions for Strykers and HMMWVs set at 75% intermediate and 25% maximum.

Vehicle load conditions for trucks set at 50% empty, 40% loaded, 10% max load.

OFF-ROAD TRAVEL ANALYSIS

ALTERNATIVE	NOMINAL LOCATION	CUMULATIVE VEH-HOURS	PERCENT OF TOTAL
PROPOSED ACTION	SCHOFIELD	18,749	16.75%
	DMR	18,589	16.61%
	KTA	19,486	17.41%
	SUBTOTAL	56,825	50.76%
	PTA	55,119	49.24%
	TOTAL	111,944	100.00%
DEDVICED I AND	aguariei b	10.740	16.750/
REDUCED LAND	SCHOFIELD	18,749	16.75%
ACQUISITION	DMR	18,589	16.61%
	KTA	19,486	17.41%
	SUBTOTAL	56,825	50.76%
	PTA	55,119	49.24%
	TOTAL	111,944	100.00%
NO ACTION	SCHOFIELD	11,466	17.37%
1,611611611	DMR	15,112	22.89%
	KTA	10,303	15.61%
	SUBTOTAL	36,882	55.86%
	PTA	29,144	44.14%
	TOTAL	66,025	100.00%
	TOTAL	00,023	100.00 /0

Notes:

Vehicle idling time for off-road travel set at twice the cumulative driving time.

Vehicle load conditions for Strykers and HMMWVs set at 75% intermediate and 25% maximum.

Vehicle load conditions for trucks set at 50% empty, 40% loaded, 10% max load.

GRAND TOTALS

	NOMINAL	CUMULATIVE	PERCENT
ALTERNATIVE	LOCATION	VEH-HOURS	OF TOTAL
ALTERIVATIVE	LOCATION	VEII-HOURS	OF TOTAL
PROPOSED ACTION	SCHOFIELD	54,354	30.52%
FROFOSED ACTION	DMR	24,894	13.98%
	KTA	24,894	13.71%
	SUBTOTAL	103,661	58.20%
	PTA	74,441	41.80%
	TOTAL	,	100.00%
	IOIAL	178,103	100.00%
REDUCED LAND	SCHOFIELD	54,354	30.52%
ACOUISITION	DMR	24,894	13.98%
ACQUISITION	KTA	,	13.71%
	SUBTOTAL	24,414 103,661	
		/	58.20%
	PTA	74,441	41.80%
	TOTAL	178,103	100.00%
NO ACTION	SCHOFIELD	36,129	32.12%
NO ACTION	DMR	,	32.12% 18.16%
	KTA	20,427	12.01%
	SUBTOTAL	13,512 70,068	62.29%
		,	
	PTA	42,416	37.71%
	TOTAL	112,484	100.00%
NET CHANGE FOR SBCT	SCHOFIELD	18,224	27.77%
	DMR	4,467	6.81%
	KTA	10,902	16.61%
	SUBTOTAL	33,594	51.20%
	PTA	32,025	48.80%
	TOTAL	65,619	100.00%
		,-	

VEHICLE MILEAGE ASSUMPTIONS, NO ACTION:

VEHICLE	NUMBER	ANNUAL USE	PER VEHICLE	ASSUMED	% VMT
TYPE	OF VEHICLES	DAYS PER VEH	MILES/USE-DAY	MI/YR/VEH	BY VEH TYPE
STRYKER	0	150	10	1,500	0.00%
HMMWV	460	180	12	2,160	78.90%
LMTV	90	175	8	1,400	10.01%
MTV	70	145	8	1,160	6.45%
HEMTT	25	60	25	1,500	2.98%
PLS, HET	14	50	30	1,500	1.67%
TOTALS	659	168	11	1,911	100.00%

VEHICLE MILEAGE ASSUMPTIONS, PROPOSED ACTION AND REDUCED LAND ACQUISITION:							
VEHICLE	NUMBER	ANNUAL USE	PER VEHICLE	ASSUMED	% VMT		
TYPE	OF VEHICLES	DAYS PER VEH	MILES/USE-DAY	MI/YR/VEH	BY VEH TYPE		
STRYKER	296	150	10	1,500	24.24%		
HMMWV	490	185	12	2,220	59.39%		
LMTV	105	180	8	1,440	8.26%		
MTV	75	150	8	1,200	4.91%		
HEMTT	25	60	25	1,500	2.05%		
PLS, HET	14	50	30	1,500	1.15%		
TOTALS	1,005	167	11	1,822	100.00%		

Notes:

HMMWV = high mobility multipurpose wheeled vehicle (humvee)

LMTV = light medium tactical vehicle (2.5 ton truck)

MTV = medium tactical vehicle (5 ton truck)

HEMTT = heavy expanded mobility tactical truck (10 ton truck)

PLS = palletized load system truck (25+ ton capacity)

HET = heavy equipment transporter (60+ ton capacity)

The high-low range of vehicle requirement estimates for individual range facilities yield fleet-wide annual average vehicle use values ranging from 37 to 301 use-days per year per vehicle.

The use estimates assumed above yield a fleet-wide weighted annual average slightly below the 169 use-day per vehicle mid-point value.

Stryker mileage split 50% on roadways, 50% off-road. Roadway type split 25% paved roads, 75% unpaved roads.

HMMWV mileage split 2/3 on roadways, 1/3 off-road. Roadway type split 50% paved roads, 50% unpaved roads.

LMTV and MTV mileage split 75% on roadways, 25% off-road. Roadway type split 50% paved roads, 50% unpaved roads.

HEMTT, PLS, and HET heavy truck mileage split 75% on roadways, 25% off-road. Roadway type split 75% paved roads, 25% unpaved roads.